



36 Draffin Road Hilton, New York 14468
Phone: 585-392-3434
Toll Free: 1-800-828-6351
Sales: sales@monroefluid.com
Technical: technical@monroefluid.com

Cool Tool II

OVERVIEW

COOL TOOL II is a universal cutting and tapping fluid that performs extremely well on ALL metals including Aluminum, Stainless Steel, exotic alloys and some plastics. COOL TOOL II does NOT contain 1,1,1- trichloroethane. COOL TOOL II contains NO ozone depleting chemicals (ODCs).

APPLICATIONS

Apply COOL TOOL II cutting and tapping fluid directly to the cutting tool using a brush, oil can or other convenient applicator. May be used for drilling, tapping, reaming, milling, turning, boring, broaching, hobbing and blanking of all metals.

MIXING

No mixing is required.

TYPICAL PROPERTIES

| | |
|-------------------------|--------------------|
| Appearance | Clear Amber liquid |
| Residual Film | Soft, oily |
| pH @ 20:1 | N/A |
| Specific Gravity @ 60°F | 0.91 ± 0.01 |
| Lbs/Gallon | 7.6 ± 0.1 |
| Flash point, PMCC | 182° (360°F) |

Material Safety Data Sheets are available for all products.
All reasonable care has been taken to ensure
that the above information is accurate as of the date of printing.